

Die Wand,
die aus der Decke kommt
... per Knopfdruck!

LOSCHWAND®
classic
GG/2-398 TLS

Announcement-text LOSCHWAND® classic
- G l a s s -
Vertikal electric partition system

LOSCHWAND® classic GG / 2 - 398 TLS

all-glass-design
with an additional telescope-rail in the middle
of the glass-elements
made from 2 pane laminated safety glass
VSG from 2 x ESG 8 mm / 10 mm thick

Length: total length between vertical guide railsmm
measurement of guide rail: 154 / 161 mm	
Length: LOSCHWAND® classic GG/2-398 TLS	max. 11000 mm
Height: Finished floor to finished ceilingmm
Höhe: LOSCHWAND® classic GG/2-398 TLS	max. 4000 mm
Special height on inquiry	
Storage Space :in the false ceilingmm
alternativ:	
below false ceiling	
"visible technology"mm
Storage space height: LOSCHWAND® classic GG/2-398 TLS	min. 650 mm
Storage space depth: LOSCHWAND® classic GG/2-398 TLS	min. 1000 mm
Size of each glass-element: Glass-strength: 17 mm	
Glass-height: 398 mm	

Operating mode:

Fully automatic and operates by push of a button or turn of a key

Technical description:

The LOSCHWAND® classic GG/2-398 TLS exists of a 2 pane of laminated safety glass, VSG from 2 x 8 mm ESG with 1,5 mm glass-foil, transparent. Colour foil, decor foil against extra charge. In closed position, there is a gap of approx. 4 mm between the elements
The elements are detained and guided by guide rails on each side and stored in a horizontal position in the magazine, normally located in the false ceiling.
The drive and safety devises are incorporated in the magazine
An up down switch or key is required to operate the partition.
The partition cannot be lifted or pushed up when in closed position.
The LOSCHWAND® classic GG/2-398 TLS is outfitted with a safety system for the elements, which will engage, when the elements exceed a certain speed while closing..

Colour of guide rails: acc. RAL-colour card

Quotation:

Delivery and assembly: _____

Extra charge for a contact element below the lowest element
in case there is something under the partition while it is closing _____

Extra charge for colour foil, decor etc. _____

Guarantee:

5 years, except electric parts after VOL 6 months with conclusion of a maintenance-contract.

Maintenance and examination:

According the lawful regulations (ZH1/494), the partition-system must be test and serviced

Maintenance cost without spare parts per year: _____

Maintenance-opening:

Openings have to be installed for the yearly service and maintenance as per LOSCHWAND® specs.

Losch Wandsysteme GmbH + Robert Bosch Strasse 9/1 + D- 72654 Neckartenzlingen
Telefon: 07127 9377- 0 + Fax: 07127 9377- 28 + e-mail: info@LOSCHWAND.de + http://www.LOSCHWAND.de

Stand : 1. Januar 2002