

Die Wand,
die aus der Decke kommt
... per Knopfdruck!

LOSCHWAND® HubWand desk

Announcement-text LOSCHWAND® HubWand - G l a s s - Vertikal electric partition system

LOSCHWAND® HubWand desk

all-glass-design
made out of 10 or 12 mm safety glass

Length: total length between vertical guide railsmm
measurement of guide rail: 39 / 59 mm	
Length: LOSCHWAND® HubWand	max. 5100 mm
Special length on inquiry	
Height: Finished desk to finished ceilingmm
Height: LOSCHWAND® HubWand	max. 1500 mm
Special height on inquiry	
Storage Space :in the false ceilingmm
Storage space height: LOSCHWAND® HubWand desk	min. 250 mm
Storage space depth: LOSCHWAND® HubWand desk	min. 600 mm

Operating mode:

Fully automatic

Technical description:

The LOSCHWAND® HubWand desk is made out of a 10 or 12 mm safety glass,
Colour foil, decor foil possible against extra charge.

The elements are detained and guided by guide rails on each side.

The drive and safety devices are incorporated in the ceiling.

A up / down switch or key switch is required to operate the LOSCHWAND® HubWand desk.

The LOSCHWAND® HubWand desk system has two safety devices.

There is a cable safety system which will stop the movement of the LOSCHWAND® HubWand desk
if there is too much or too little torque on the drive train. (standard)

Optional: Pressure sensing strip will stop the closing movement of the LOSCHWAND® HubWand desk.
In case there is something under the glass.

Pressure sensing strip against extra charge.

Colour of guide rails: acc. RAL-colour card

Quotation::

Delivery and assembly: _____

Extra charge for "visible technology" _____

Extra charge for colour foil, decor etc. _____

Guarantee:

5 years, except electric parts after VOL 6 months with conclusion of a maintenance-contract.

Maintenance and examination:

According to the lawful regulations (ZH1/494), the partition-system must be tested and serviced

Maintenance cost without spare parts per year: _____

Maintenance-opening:

Openings have to be installed for the yearly service and maintenance as
per LOSCHWAND® specs.