

Die Wand,
die aus der Decke kommt
... per Knopfdruck!

LOSCHWAND®
classic
S67/SD

Announcement-text LOSCHWAND® classic
- Aluminium -
Vertikal electric partition system

LOSCHWAND® classic S 67 / SD

Aluminium-profile with div.inlay
Soundproof RW 42 dB (laboratory value)

Length: total length between vertical guide railsmm
measurement of guide rail: 80 / 125 mm	
Length: LOSCHWAND® classic S 67/SD	max. 9000 mm
Height: Finished floor to finished ceiling mm
Height: LOSCHWAND® classic S 67/SD	max. 3450 mm
Special-height on inquiry	
Storage space: in the false ceilingmm
alternative:	
below false ceiling	
"visible technology"mm
Storage space height: LOSCHWAND® classic S 67/SD	min. 420 mm
Storage space depth: LOSCHWAND® classic S 67/SD	min. 1250 mm
Size of each element: element-strength: 67 mm	
element-height: 204 mm	

Surface:

Standard: Powder coating acc. RAL-colour card
Alternatively: wood-veneer, Resopal, mirror etc.

Operating mode:

Fully automatic

Technical description:

The LOSCHWAND® classic S 67/SD exists from an aluminium element partition system that interlocks in the closed position, with a soundproof value of 42 dB. The elements are detained and guided by guide rails on each side. The total length can be up to 9000 mm incl. guide rails and a height of 3450 mm (not included storage compartment „magazine“). The elements are stored in a horizontal position in the magazine, normally located in the false ceiling. The drive and safety devices are incorporated in the magazine. An up down switch or key is required to operate the partition. The partition can not be lifted or pushed up when in closed position, and is rated at „Burglary-inhibiting“. The partition system has two safety devices. The safety system for the elements, which will engage, when the elements exceed a certain speed while closing, and a contact element below the lowest element in case there is something under the partition, while it is closing.

Quotation::

Delivery and assembly: _____

Extra charge for "visible technology" _____

Extra charge for alternative surface: _____

Guarantee:

5 years, except electric parts after VOL 6 months with conclusion of a maintenance-contract.

Maintenance and examination:

According the lawful regulations (ZH1/494), the partition-system must be test and serviced

Maintenance cost without spare parts per year: _____

Maintenance-opening:

Openings have to be installed for the yearly service and maintenance as

Losch Wandsysteme GmbH + Robert Bosch Strasse 9/1 + D- 72654 Neckartenzlingen
Telefon: 07127 9377- 0 + Fax: 07127 9377- 28 + e-mail: info@LOSCHWAND.de + http://www.LOSCHWAND.de

Stand : 1. Januar 2002

Die Wand,
die aus der Decke kommt
... per Knopfdruck!

LOSCHWAND®
classic

per LOSCHWAND® specs.